

## Product Feature of the Month Clockaudio's C002E-RF and C009E-RF

Specifically designed for huddle room applications, the COO2E-RF and COO9E-RF have a discrete and classy look. Both can easily be set in the middle of a round or square table, capturing every participant around the table. They are very low profile and come with rubber shock mounting pads.



The COO2E-RF and the COO9E-RF are made out of solid brass. They are basically the same microphone, but with an approximate weight ratio of 1:4. Both have an In-Line 9-48V Phantom Power adaptor and RF filtering enclosed in the XLR output connector

The COO2 is 3" in diameter, about the size of a hockey puck, and only ½ inch thick at its highest point in the center and weighs just under a pound (400 grams). The COO9, also at ½" thick, is a little over 6 inches in diameter. Designed for larger surfaces, with a 4X body weight of the COO2 (almost 4 pounds or 1.74Kg) it can absorb more vibrations generated from having more participants at the same table.



Both mics have a condenser capsule and require phantom power. With a sensitivity of -42.5dB at 1KHz, give or take 2 dB 0dB = 1V/Pa. Offering the flattest frequency response of all Clockaudio microphones, they are ideal for capturing speech in smaller, low noise environments and capture speech quite intelligibly.

# # #

as featured in CA June Newsletter

clockaudio LTD. UK info@clockaudio.co.uk CLOCKAUDIO NORTH AMERICA INC. info@clockaudio.com CLOCKAUDIO PTE LTD. SINGAPORE info@clockaudio.com.sg